

## Sealant Selection

**Crafco Crack Sealing** - This process should be performed on pavements that are in good condition. That is defined as a pavement with a sound base and exhibits distress in the form of thermal or working cracks spaced at over 20 feet. The procedure consists of routing and sealing transverse cracks in order to prevent moisture from entering and deteriorating the sub-base, and incompressible material from interfering with thermal movement. See the Crafco Installation Instructions for your chosen sealant to get specific directions on preparation and application. If properly designed and installed, the expected life of this procedure is typically 5 to 7 years, in most cases.

**Crafco Performance Crack Fillers** - This procedure consists of filling closely spaced or non-working cracks to reduce moisture penetration into the sub-base of the pavement. If moisture is not checked, catastrophic pavement failure such as potholes will form. Another reason for crack filling is to stop crack raveling. Crack filling is a very cost-effective method of pavement repair that will add years to its life. Crack fill pavements, that are in fair to poor condition, on a regular basis to maintain their condition. If properly designed and installed, the expected life of this procedure, in most cases, is 3 to 5 years.

**Crafco Joint Sealing** - Sealing concrete pavement joints is required to stop moisture from entering and deteriorating the sub-base of the pavement and decrease spalling. The most cost-effective method of ensuring optimum performance of a PCC pavement is by constructing a sound joint seal system that will last. If properly designed and installed, the expected life of this procedure is typically 5 to 7 years.

### Sealant Selection Guide

Sealant Selection Guide		HEAT TYPE								ASTM		AASHTO				Fed FAA		SPECIALTY						
PART NUMBER	PRODUCT NAME	DIRECT FIRE	OIL JACKETED	D 690 TYPE I	D 690 TYPE II	D 690 TYPE III	D 690 TYPE IV	D 5078	D 5895	M324 TYPE I (M 173)	M324 TYPE II (M 301)	M324 TYPE III (M 301)	M324 TYPE IV (M 301)	MODIFIED AASHTO	SS-S164	SS-S1401C	P 605	PARKING LOT	RECYCLED RUBBER	FIBERIZED	WATERPROOFING	ADHESIVE	OTHER SPECS	
34200 - Parking Lot Sealant		■																■						
34201 - RoadSaver 201		■	■	■						■	■			■	■		■	■						
34202 - Parking Lot Sealant Type 1		■																■						
34211 - RoadSaver 211		■	■							■				■										
34220 - RoadSaver 220		■	■	■						■	■			■			■							VIRGIN POLYMER
34221 - RoadSaver 221		■	■	■						■	■			■										
34222 - RoadSaver 222		■	■	■	■					■	■	■		■	■		■							
34231 - RoadSaver 231		■					■		■				■											LOW MODULUS
34232 - Asphalt Rubber Type 2							■												■					
34234 - Asphalt Rubber Type 4		■																	■					
34240 - Asphalt Rubber Type 1		■					■													■				
34241 - Asphalt Rubber Plus		■	■						■					■						■				
34244 - Asphalt Rubber Plus Type 2		■	■						■				■	■						■				
34250 - PolyFiber Type 3		■	■											■	■					■				CRAFCO SPECIFICATION
34251 - PolyFiber Type 4		■																		■				CRAFCO SPECIFICATION
34500 - High Slope		■																		■	■			CRAFCO SPECIFICATION
34515 - RoadSaver 515		■	■						■					■	■									
34516 - PolyFlex Type 1		■																	■					CRAFCO SPECIFICATION
34517 - Crafco DF		■	■																					CRAFCO SPECIFICATION
34518 - PolyFlex Type 2		■																	■					CRAFCO SPECIFICATION
34519 - Fiber Asphalt		■																		■				CRAFCO SPECIFICATION
34521 - PolyFlex Type 3		■																		■				CRAFCO SPECIFICATION
34522 - RoadSaver 522		■																						LOW MODULUS, CRAFCO SPECIFICATION
34524 - Pavement Joint Adhesive		■																			■	■		CRAFCO SPECIFICATION
34526 - PolyFlex Type 4		■	■																	■				CRAFCO SPECIFICATION
34532 - SuperFlex		■	■																	■				CRAFCO SPECIFICATION
34533 - SuperFlex HT		■	■																	■				CRAFCO SPECIFICATION
34534 - RoadSaver 534		■	■	■						■	■			■			■							LOW TACK
34543 - RoadSaver Low Tack		■	■																	■				CRAFCO SPECIFICATION
34546 - RoadSaver Low Tack Type 2		■																						CRAFCO SPECIFICATION

All Crafco Products meet or exceed the specifications listed.

©2016 Crafco, Inc. November #A1032

phone: (800) 528-8242 • email: sales@crafco.com • web: crafco.com