



CARUSOL® liquid permanganate is an effective oxidant recommended for potable drinking water applications that require a concentrated permanganate solution. Applications include iron and manganese reduction, taste and odor control, disinfection by-product reduction, color reduction, and radium reduction.

PRODUCT SPECIFICATIONS

Assay	19.5 - 21.5% as NaMnO₄
pH	5.0 - 8.0
Solubility in Water	Miscible with water in all proportions

Standards and Specifications

CARUSOL meets:

AWWA Standard B603-10

EN: 15482 - 10 mg/L max

ANSI/NSF 60

KIWA- Product certification no. K83927 - 17 mg/L max

NSF Maximum Use Level 176 mg/L



CHEMICAL/PHYSICAL DATA

Formula	NaMnO ₄
Appearance	Dark Purple Solution
Specific Gravity	1.15 - 1.17
Freezing Point	21° F (-6° C)

APPLICATIONS

- Drinking Water Purification
- Iron/Manganese Oxidation
- Taste and Odor Control
- Preoxidant for THM and HAA Control
- Hydrogen Sulfide Control
- Radium Removal
- Color Removal

BENEFITS

- Concentrated liquid oxidant
- More precise dosing of chemical
- Feed equipment is simplified
- Consistent concentration

SHIPPING CONTAINERS

5-gallon (20-L) Jerrican

(UN Specification: UN3H1/Y1.8/100) Made of high density polyethylene (HDPE). Weighs 3.3 lb (1.5 kg). The net weight is 48.5 lb (22 kg). The jerrican stands approximately 13.4 in. tall, 9.4 in. wide, and 13.0 in. deep (33.9 cm high, 23.8 cm wide, and 33.0 cm. deep).

55-gallon (208.2L) Closed Head HDPE Drum

(UN Specifications: UN1H1/Y1.9/100) Made of high density polyethylene (HDPE). Weighs 20.5 lb (9.3kg). The net weight is 533.5 lb (241.9 kg). The drum stands approximately 35.1 in. tall and has an outside diameter of 23.4 in. (89.1 cm tall, OD 59.4 cm).

275-gallon (1041 L) IBC (Intermediate Bulk Container)

(UN Specification: UN31HA1/Y1.9/100) They are also marked "MX" for multi-trip IBC. Weighs 123 lb (55.8 kg). The net weight is 2550 lb (1160 kg). The IBC contains 263 gallons of product. The IBC dimensions are 45.3 in. (114.9 cm) high, 47.3 in. (120.0 cm) long, and 39.4 in. (100.0 cm) wide. The IBC has a 2 in. butterfly valve with NPT threads in bottom sump.

Bulk Shipping Quantities from 3000-4200 gallons are available.

HANDLING, STORAGE, AND INCOMPATIBILITY

Like any strong oxidant, CARUSOL liquid permanganate should be handled with care. Protective equipment during handling should include face shields and/or goggles, rubber or plastic gloves, and rubber or plastic apron. If clothing becomes spotted, wash off immediately; spontaneous ignition can occur with cloth or paper. In cases where significant exposure exists, use of the appropriate NIOSH-MSHA dust or mist respirator is recommended.

Store in accordance with NFPA (National Fire Protection Association) Code 430 requirements for Class II Oxidizers. The product should be stored in a cool, dry area in closed containers. Concrete floors are preferred. Avoid wooden decks. Spillage should be collected and disposed of properly. Contain and dilute spillage to approximately 6% with water, and then reduce with sodium thiosulfate, a bisulfite, or ferrous salt solution. The bisulfite or ferrous salt may require some dilute sulfuric acid (10% w/w) to promote reduction. Neutralize with sodium carbonate to neutral pH, if acid was used. Deposit sludge in an approved landfill or, where permitted, drain into sewer with large quantities of water.

CARUS CORPORATION

CORPORATE HEADQUARTERS | 315 Fifth Street, Peru IL 61354 | Tel +1.815.223.1500 / 1-800-435-6856 | Fax +1.815.224.6697 | Web: www.caruscorporation.com | E-mail: salesmkt@caruscorporation.com

CARUS EUROPE | Calle Rosal 4, 1-B | Oviedo, Spain 33009 | Tel +34.985.785.513 / Fax +34.985.785.510

ONE COMPANY. ENDLESS SOLUTIONS

The information contained herein is accurate to the best of our knowledge. However, data, safety standards and government regulations are subject to change; and the conditions of handling, use or misuse of the product are beyond our control. Carus Corporation makes no warranty, either expressed or implied, including any warranties of merchantability and fitness for a particular purpose. Carus also disclaims all liability for reliance on the completeness or confirming accuracy of any information included herein. Users should satisfy themselves that they are aware of all current data relevant to their particular use(s).

Carus and Design is a registered service mark of Carus Corporation. CARUSOL is a registered trademark of Carus Corporation. ResponsibleCare® is a registered service mark of the American Chemistry Council.

Copyright 2012
rev. 06/19
Form LX 11006



RESPONSIBLE CARE®
OUR COMMITMENT TO SUSTAINABILITY

CARUS®





HANDLING, STORAGE Cont.

As an oxidant, the product itself is non-combustible, but will accelerate the burning of combustible materials. Therefore, contact with all combustible materials and/or chemicals must be avoided. These include but are not limited to: wood, cloth, organic chemicals, and charcoal. Avoid contact with acids, peroxides, sulfites, oxalates, and all other oxidizable inorganic chemicals. During contact with hydrochloric acid, chlorine is liberated. Consult the SDS for additional safety information.

SHIPPING

CARUSOL® liquid permanganate is classified and listed as an oxidizer by PHMSA (Pipeline and Hazardous Materials Safety Administration, Department of Transportation, in 49 CFR Subchapter C, HMR (Hazardous Materials Regulation), Part 172.101 HMT (Hazardous Materials Table).

Proper Shipping Name: Permanganates, inorganics, aqueous solution n.o.s. (Contains sodium permanganate).

Hazard Class: 5.1

Identification Number: UN 3214

SHIPPING CONTINUED

Packaging Group: II

Label Requirements: Oxidizer, 5.1

Packaging Requirements: 49 CFR Parts 171 to 180

Sections: 173.152, 173.202, 173.242

COMPATIBILITY INFORMATION

CARUSOL liquid permanganate is compatible with many metals and synthetic materials. Natural rubbers and fibers are often incompatible. Solution pH and temperature are also important factors. The material selected for use with liquid permanganate must also be compatible with any kind of acid or alkali being used. In neutral and alkaline solutions, sodium permanganate is not corrosive to carbon steel and 316 stainless steel; however, chloride corrosion of metals may be accelerated when an oxidant such as liquid permanganate is present in solution. Plastics such as Teflon, polypropylene, and HDPE are also compatible with liquid permanganate.

Aluminum, zinc, copper, lead, and alloys containing these metals may be (slightly) affected by sodium permanganate solutions. Actual corrosion or compatibility studies should be made under the conditions in which permanganate will be used prior to use.

CARUS VALUE ADDED

LABORATORY SUPPORT

Carus Corporation has technical assistance available to answer questions, evaluate treatment alternatives, and perform laboratory testing. Our laboratory capabilities include: consulting, treatability studies, feasibility studies, and analytical services.

FIELD SERVICES

As an integral part of our technical support, Carus provides extensive on-site treatment assistance. We offer full application services, including technical expertise, supervision, testing, and feed equipment design and installation in order to accomplish a successful evaluation and/or application.

ENGINEERED SYSTEMS AND EQUIPMENT SERVICES

Various options and accessories are available to meet a wide range of applications. Custom-engineered feed systems are complete, pre-engineered and prepackaged systems. System designs are customized to meet specific applications and customer needs. CARUSOL liquid permanganate eliminates the need to prepare solutions from dry powder and can be fed with simple dosing pumps.

CARUS CORPORATION

During its 100-year history, Carus' ongoing emphasis on research and development, technical support, and customer service has enabled the company to become the world leader in permanganate, manganese, oxidation, and base-metal catalyst technologies.

Permanganate products are not registered as a pesticide under the Federal Insecticide, Fungicide and Rodenticide Act administered by U.S. EPA or similar state laws. Use as a pesticide is not government approved.

CARUS CORPORATION

ONE COMPANY. ENDLESS SOLUTIONS

CORPORATE HEADQUARTERS | 315 Fifth Street, Peru IL 61354 | Tel +1.815.223.1500 / 1-800-435-6856 | Fax +1.815.224.6697 | Web: www.caruscorporation.com | E-mail: salesmkt@caruscorporation.com
CARUS EUROPE | Calle Rosal 4, 1-B | Oviedo, Spain 33009 | Tel +34.985.785.513 / Fax +34.985.785.510

The information contained herein is accurate to the best of our knowledge. However, data, safety standards and government regulations are subject to change; and the conditions of handling, use or misuse of the product are beyond our control. Carus Corporation makes no warranty, either expressed or implied, including any warranties of merchantability and fitness for a particular purpose. Carus also disclaims all liability for reliance on the completeness or confirming accuracy of any information included herein. Users should satisfy themselves that they are aware of all current data relevant to their particular use(s).

Carus and Design is a registered service mark of Carus Corporation. CARUSOL is a registered trademark of Carus Corporation. ResponsibleCare® is a registered service mark of the American Chemistry Council.



Copyright 2012
rev. 06/19
Form LX 11006

CARUS®