Rehrig Pacific Company
SINCE 1913

Proposal to:
Capitol Region Purchasing Council
ITB#761
Recycling Bins
Manufacturer's Specification Sheets

DUE:
February 20, **2024 @ 9:00 AM**

Prepared by:
Stephen Mullis
Territory Manager
1738 West 20th St.
Erie, PA. 16502
Cell: (781) 264-5251
Email: SMullis@Rehrig.com

95 Gallon EnviroGuard Roll Out Cart Specifications

Meets and/or exceeds all ANSI Standards for Type B & G containers





Specifications	IN/LB	CM/KG
Capacity (Gallons / Liters)	95 Gal	360 L
Overall Depth (D)	33.3	84.5
Overall Width (W)	29.2	74.1
Overall Height With Lid (H)	43.5	110.4
Lift Skirt Height (H1)	33	83.8
Upper Lift Skirt Width (W1)	9.5	24.1
Catch Bar Width (W2)	5.6	14.2
Handle Height (H2)	40.6	103.1
Distance Between Skirt & Catch Bar (H3)	15.2	38.7
Resin Weight	32	14.5
Assembled Weight	35	15.8
Gripping Diameter	28.1	71.4
Nest Increment	5.7	14.4
Carts Per Stack	13	
53' Trailer Quantity	702	



Decoration Areas	WIDTH (IN)	HEIGHT (IN)
Side Brand - Hot Stamp (B1)	11.5	7.5
Barcode & Serial Number (B2)	9.75	1.25
Lid Hot Stamp Brand (B3)	11	2.25
4 color In Mold Label or Hot Stamp (B4)	8	12

Specifications

- Manufacturing Process - Injection Molding
- Material - High-density polyethylene resin (HDPE) Manufacturer: Exxon or Dow Type: HD-6605 Recycled Content of up to 30% PCR Color pigment and ultraviolet inhibitor compounded at 1.5% - 2% by weight
- Wall Thickness - Cart Nominal: 0.165" Cart Critical Wear Points: 0.19" (Drag Rail and Axle Box) Lid Nominal: 0.140"
- Branding - Hot stamp process permanently imprints logos on cart side body and lid. IML capabilities for the lid
- Visible Bar Code/Serial Number when stacked
- Lid Opening - 270 degrees
- Lid Assembly - Carts are shipped with the lids already attached
- Catch Bar - 1" corrosion resistant zinc plated steel allows favorable nesting ratios. Fully enclosed and doesn't penetrate the cart body.
- Axle - High strength, low alloy steel, 3/4" x 22.625", zinc plated or powder coated equivalent for corrosion protection
- Wheels - 10" Wheels, snap-on with 1.4" integrated spacers. Treaded wheel options are available and subject to additional cost and lead time.
- Handle - Handle attachments are integrally molded part of the container body with a gripping area of 16". Clearance between the cart body and the inside edge of the handle has been maximized to provide optimum control of a fully loaded cart
- Lift System Compatibility - American semi-automated bar-locking lifters and fully automated arm lifters.
- ANSI load rating = 332.5 lbs. (3.5 lbs. Per gallon)
- RFID Enabled Option
- 10 Year warranty
- Decoration Areas: Brands are subject to one time set up fees and IML pricing is dependent on size and the number of colors.

vision

Corporate Headquarte
4010 East 26th St., Los Angeles, CA 90058
(323) 262-5145

Web: www.rehrigpacific.com

Rehrig Pacific Company
SINCE 1913

A FAMILY TRADITION OF GROWTH, SERVICE AND INNOVATION

95 EG REV NC

© 2020 Rehrig Pacific Company.

65 Gallon EnviroGuard Roll Out Cart Specifications

Meets and/or exceeds all ANSI Standards for Type B & G containers



Specifications	IN/LB	CM/KG
Capacity (Gallons/Liters)	65 Gal	246 L
Overall Depth (D)	27.0	68.58
Overall Width (W)	26.5	67.31
Overall Height with Lid (H)	43.6	110.74
Lift Skirt Height (H1)	33.25	84.46
Upper Lift Skirt Width (W1)	9.375	23.81
Catch Bar Width (W2)	5.715	14.52
Handle Height (H2)	40.65	103.25
Distance Between Skirt & Catch Bar (H3)	15.25	38.74
Resin Weight	25.5	11.5
Assembled Weight	30.1	13.65
Gripping Diameter	23.15	58.80
Nest Increment	5.7	14.4
Carts Per Stack 13	13	
53' Trailer Quantity	936	

Decoration Areas	WIDTH (IN)	HEIGHT (IN)
Side Brand - Hot Stamp (B1)	11.5	7.5
Barcode & Serial Number (B2)	9.75	1.25
Lid Hot Stamp Brand (B3)	11.0	2.25
4 color In Mold Label or Hot Stamp (B4)	12.0	8.0

Specifications

- Manufacturing Process - Injection Molding
- Material - High-density polyethylene resin (HDPE) Manufacturer: Exxon or Dow Type: HD-6605 Recycled Content of up to 30% PCR Color pigment and ultraviolet inhibitor compounded at 1.5% - 2% by weight
- Wall Thickness - Cart Nominal: 0.155" Cart Critical Wear Points: 0.19" (Drag Rail and Axle Box) Lid Nominal: 0.140"
- Branding - Hot stamp process permanently imprints logos on cart side body and lid. IML capabilities for the lid
- Visible Bar Code/Serial Number when stacked
- Lid Opening - 270 degrees
- Lid Assembly - Carts are shipped with the lids already attached
- Catch Bar - 1" corrosion resistant zinc plated steel allows favorable nesting ratios. Fully enclosed and doesn't penetrate the cart body.
- Axle - High strength, low alloy steel, 3/4" x 22.625", zinc plated or powder coated equivalent for corrosion protection
- Wheels - 10" Wheels, snap-on with 1.4" integrated spacers. Treaded wheel options are available and subject to additional cost and lead time.
- Handle - Handle attachments are integrally molded part of the container body with a gripping area of 16". Clearance between the cart body and the inside edge of the handle has been maximized to provide optimum control of a fully loaded cart
- Lift System Compatibility - American semi-automated bar-locking lifters and fully automated arm lifters.
- ANSI load rating = 227.5 lbs. (3.5 lbs. Per gallon)
- RFID Enabled Option
- 10 Year warranty
- Decoration Areas: Brands are subject to one time set up fees and IML pricing is dependent on size and the number of colors.

Corporate Headquarters
4010 East 26th St., Los Angeles, CA 90058
(800) 421-6244 • (323) 262-5145

Web: www.rehrigpacific.com

Rehrig Pacific Company
SINCE 1913

A FAMILY TRADITION OF GROWTH, SERVICE AND INNOVATION

© 2020 Rehrig Pacific Company.

Proposal to:

Capitol Region Purchasing Council
ITB#761 Recycling Bins
Manufacturer's Specification Sheets
DUE: February 20 2024 9:00 AM

Prepared by:

Stephen Mullis
Territory Manager
1738 West 20th
Erie, PA. 16502
Cell: (781) 264-5251
Email: SMullis@Rehrig.com